

April 20, 2022

Ian Freeman Covia – Best Sand 11830 Ravenna Road Chardon, OH 44024

TSD File #22040060

Enclosed are the results of the Signature 700 sample received by our laboratory on 4/14/2022 from Best Chardon. This sample was tested as received for potential use as bunker sand. Bunker sand criteria published in a 2020 issue of the USGA Green Section Record are referenced in this report.

The particle size test results indicate that the sample is uniformly graded sand with most of the particles in the coarse to fine sand size fractions. The particle size results meet bunker sand guidelines, but are outside of the USGA putting green recommendations. The gradation suggests the sand may present a layering risk if splashed from green-side bunkers onto some putting graded greens.

The sand particle shape is angular to subrounded. Generally angular sands are preferred for bunkers.

There is no crusting of the sand after wetting and drying. This suggests that bunkers with this sand in place shouldn't require significant raking after rainfall or irrigation events.

A minimum infiltration rate of 30 inches per hour is generally recommended for bunker sand, though some construction methods may differ. The sand has infiltration rate that is similar to this minimum.

To measure the potential of a sand to produce fried egg lies or buried balls, resistance of the sand to ball penetration is measured with a penetrometer. The sample has a penetrometer reading of 3.0 kg/cm². While there are varying assessments of this test, results above 2.4 kg/cm² are generally considered more desirable as they suggest potential for fewer instances of buried lies.

The sample has an angle of repose of 32 degrees, with a straight pile shape.

Despite this testing, bunker sand selection is highly subjective. Aside from playability, factors such as color and aesthetics are often weighed in the decision process. We recommend that interested parties visit a club with the sand in use, play into and out of it, and see how they like it.

If you have any questions or need further assistance, please contact us. Samples are generally kept on the premises for 45 days after report date. Thank you for using Turf & Soil Diagnostics, Inc.

Sam Ferro President





Covia Ian Freeman 11830 Ravenna Rd. Chardon, OH 44024 Date Received Apr-14-2022

Date Reported Apr-20-2022

Facility Best Chardon

Bunker Sand Evaluation*

							% Retained mm (US sieve)					
Lab ID#	Sample Name	% Sand	% Silt	% Clay	Gravel	Gravel	V. Coarse	Coarse	Medium	Fine	Fine	V. Fine
		2.0 - 0.05 mm	0.05-0.002mm	< 0.002mm	4.0 (5)	2.0 (10)	1.0 (18)	0.5 (35)	0.25 (60)	0.15 (100)	0.10 (140)	0.05 (270)
22040060-3	Signature 900	97.2	1.1	< 1.0	0.0	1.5	12.8	21.2	37.4	19.9	4.2	1.7
Bunker Sand Guidelines ¹		≤ 3%			≤ 2%		≤ 15%	78 - 100% ≤ 5			≤ 5%	
USGA Recommendations for Greens		≥ 92%	≤ 5% Silt	≤ 3% Clay	0%	≤ 3% Gravel ≤ 10% Combined		≥ 60% Combined ≤ 20%		≤ 5°	%***	

Lab ID#	Sample Name	Uniformity Coefficient Cu	D15 mm	D50 mm	D85 mm	Shape Angularity	Shape Sphericity	USDA Textural Classification	Acid Reaction	Infiltration Rate** in/hr	Infiltration Rate** cm/hr	Bulk Density g/cc
22040060-3	Signature 900	2.9	0.18	0.38	0.98	Angular to Sub-Rounded	Low to High	Sand	None	27.9	70.9	1.58
Bunker Sand Guidelines ¹		2.0 - 5.0	-	-	-	-	-	-	-	> 30	> 75	-

USGA Rootzone Coefficient of Uniformity Recommendations: 1.8 to 3.5 for Mixes with Peat; 2.0 to 3.5 for Mixes with Inorganic Amendment or Pure Sand.

**ASTI	M F18	315 30	cm 1	ension

				Penetrometer	Angle of Repose		
Lab ID#	Sample Name	Dry Color	Crusting	Value kg/cm²	Angle (°)	Shape of Pile	
22040060-3	Signature 900	2.5Y 8/2 Pale Brown	None	3.0	32	Straight	


^{*}ASTM F1632 Method B, Determination of Size Factors SOP, & Bunker Sand SOP

Samples were tested as received and comments pertain only to the samples shown.

This report may not be reproduced in part, but only in full.

Sample condition upon receipt was normal.

Samples were received with a transmittal letter.



Photomicrograph of Lab ID 22040060-3 Signature 900.

Reviewed by _____

^{***}Maximum of 10% combined on Very Fine Sand, Silt, and Clay fractions.

¹ USGA Green Section Record Volume 58, Issue 11, June 2020